


BEM-D

BIMETALLIC BUTT CONNECTORS (AL-CU)



All rights reserved.

Order Code	Cable Section (mm ²)	Dimensions							Box Pcs.	Box Weight	Parcel Pcs.	Box Weight
		D1	D4	d1	d4	L1	L2	L				
BEM-D/010-006	10 / 6	5,5	10,0	5,0	9,0	32,0	25,0	70,0	140	~2,6 kg.	1.400	~26,0 kg.
BEM-D/016-010	16 / 10	5,5	10,0	5,5	9,0	35,0	28,0	75,0	140	~2,5 kg.	1.400	~25,0 kg.
BEM-D/025-010	25 / 10	7,0	12,0	5,5	9,0	37,0	28,0	78,0	100	~2,2 kg.	1.000	~22,0 kg.
BEM-D/025-016	25 / 16	7,0	12,0	6,0	10,0	37,0	30,0	80,0	100	~2,6 kg.	1.000	~26,0 kg.
BEM-D/025-025	25 / 25	7,0	12,0	7,0	11,0	37,0	28,0	82,0	100	~3,0 kg.	1.000	~30,0 kg.
BEM-D/035-016	35 / 16	8,5	14,0	6,0	10,0	44,0	30,0	88,0	70	~2,2 kg.	700	~22,0 kg.
BEM-D/035-025	35 / 25	8,5	14,0	7,0	11,0	44,0	32,0	90,0	70	~2,3 kg.	700	~23,0 kg.
BEM-D/035-035	35 / 35	8,5	14,0	8,5	12,0	44,0	32,0	90,0	60	~2,4 kg.	600	~24,0 kg.
BEM-D/050-025	50 / 25	9,5	16,0	7,0	11,0	45,0	32,0	90,0	50	~2,5 kg.	700	~25,0 kg.
BEM-D/050-035	50 / 35	9,5	16,0	8,5	12,0	45,0	34,0	95,0	50	~2,6 kg.	500	~26,0 kg.
BEM-D/050-050	50 / 50	9,5	16,0	9,5	14,0	45,0	35,0	95,0	40	~2,8 kg.	400	~28,0 kg.
BEM-D/070-035	70 / 35	12,0	18,0	8,5	12,0	46,0	34,0	100,0	35	~2,0 kg.	350	~20,0 kg.
BEM-D/070-050	70 / 50	12,0	18,0	9,5	14,0	46,0	35,0	100,0	35	~2,1 kg.	350	~21,0 kg.
BEM-D/095-035	95 / 35	13,0	21,0	8,5	12,0	51,0	34,0	100,0	25	~1,3 kg.	250	~13,0 kg.
BEM-D/095-050	95 / 50	13,0	21,0	9,5	14,0	51,0	35,0	105,0	20	~1,3 kg.	200	~13,0 kg.
BEM-D/095-070	95 / 70	13,0	21,0	12,0	16,0	51,0	41,0	110,0	20	~1,4 kg.	200	~14,0 kg.
BEM-D/120-095	120 / 95	15,0	23,0	13,0	18,0	52,0	43,0	112,0	15	~1,5 kg.	150	~15,0 kg.
BEM-D/150-070	150 / 70	16,0	25,0	12,0	16,0	54,0	41,0	113,0	12	~1,5 kg.	120	~15,0 kg.
BEM-D/150-095	150 / 95	16,0	25,0	13,0	18,0	54,0	43,0	117,0	12	~1,5 kg.	120	~15,0 kg.
BEM-D/150-120	150 / 120	16,0	25,0	15,0	20,0	54,0	44,0	118,0	12	~2,0 kg.	120	~20,0 kg.
BEM-D/185-150	185 / 150	18,0	27,0	16,0	22,0	58,0	47,0	125,0	12	~1,9 kg.	120	~19,0 kg.
BEM-D/240-150	240 / 150	20,0	30,0	16,0	22,0	60,0	47,0	125,0	8	~1,7 kg.	80	~17,0 kg.
BEM-D/240-185	240 / 185	20,0	30,0	18,0	25,0	60,0	48,0	130,0	8	~1,8 kg.	80	~18,0 kg.
BEM-D/300-240	300 / 240	23,0	34,0	20,0	27,0	65,0	55,0	140,0	6	~2,3 kg.	60	~23,0 kg.
BEM-D/400-240	400 / 240	26,0	38,0	20,0	27,0	70,0	55,0	145,0	6	~1,8 kg.	60	~18,0 kg.
BEM-D/400-300	400 / 300	26,0	38,0	24,0	30,0	70,0	60,0	150,0	6	~1,9 kg.	60	~19,0 kg.
BEM-D/500-400	500 / 400	29,0	42,0	26,0	34,0	75,0	65,0	160,0	4	~1,8 kg.	40	~18,0 kg.
BEM-D/625-500	625 / 500	34,0	54,0	30,0	38,0	80,0	70,0	170,0	1	~0,7 kg.	10	~7,0 kg.

BEM-D SPECIFICATIONS

MATERIAL	ELECTROLYTIC COPPER / ALUMINIUM
COATING	NATURAL BRIGHT
JOINT	CLAMP COUPLING

