



BKP-D

BIMETALLIC CABLE LUGS (AL-CU)

All rights reserved.

Order Code	Cable Section (mm ²)	Bolt	Dimensions					Box Pcs.	Box Weight	Parcel Pcs.	Box Weight
			d1	d4	a	d2	L				
BKP-D/016-M08	16	M08	6,0	16,0	42,0	8,5	90,0	40	~2,1 kg.	400	~21,0 kg.
BKP-D/016-M10		M10	6,0	16,0	42,0	10,5	90,0	40	~2,1 kg.	400	~21,0 kg.
BKP-D/016-M12/SD		M12	6,0	16,0	42,0	13,0	90,0	40	~2,1 kg.	400	~21,0 kg.
BKP-D/025-M08	25	M08	7,0	16,0	42,0	8,5	90,0	40	~2,0 kg.	400	~20,0 kg.
BKP-D/025-M10		M10	7,0	16,0	42,0	10,5	90,0	40	~2,0 kg.	400	~20,0 kg.
BKP-D/025-M12/SD		M12	7,0	16,0	42,0	13,0	90,0	40	~2,0 kg.	400	~20,0 kg.
BKP-D/035-M08	35	M08	8,5	16,0	42,0	8,5	90,0	40	~2,0 kg.	400	~20,0 kg.
BKP-D/035-M10		M10	8,5	16,0	42,0	10,5	90,0	40	~2,0 kg.	400	~20,0 kg.
BKP-D/035-M12/SD		M12	8,5	16,0	42,0	13,0	90,0	40	~2,0 kg.	400	~20,0 kg.
BKP-D/050-M08	50	M08	9,6	20,0	43,0	8,5	90,0	30	~2,0 kg.	300	~20,0 kg.
BKP-D/050-M10		M10	9,6	20,0	43,0	10,5	90,0	30	~2,0 kg.	300	~20,0 kg.
BKP-D/050-M12/SD		M12	9,6	20,0	43,0	13,0	90,0	30	~2,0 kg.	300	~20,0 kg.
BKP-D/070-M08	70	M08	11,5	20,0	43,0	8,5	90,0	30	~2,0 kg.	300	~20,0 kg.
BKP-D/070-M10		M10	11,5	20,0	43,0	10,5	90,0	30	~2,0 kg.	300	~20,0 kg.
BKP-D/070-M12/SD		M12	11,5	20,0	43,0	13,0	90,0	30	~2,0 kg.	300	~20,0 kg.
BKP-D/095-M08	95	M08	13,5	20,0	43,0	8,5	90,0	30	~1,8 kg.	300	~18,0 kg.
BKP-D/095-M10		M10	13,5	20,0	43,0	10,5	90,0	30	~1,8 kg.	300	~18,0 kg.
BKP-D/095-M12/SD		M12	13,5	20,0	43,0	13,0	90,0	30	~1,8 kg.	300	~18,0 kg.
BKP-D/120-M08	120	M08	15,0	25,0	60,0	8,5	115,0	15	~1,9 kg.	150	~19,0 kg.
BKP-D/120-M10		M10	15,0	25,0	60,0	10,5	115,0	15	~1,9 kg.	150	~19,0 kg.
BKP-D/120-M12/SD		M12	15,0	25,0	60,0	13,0	115,0	15	~1,9 kg.	150	~19,0 kg.
BKP-D/150-M08	150	M08	16,6	25,0	60,0	8,5	115,0	15	~1,8 kg.	150	~18,0 kg.
BKP-D/150-M10		M10	16,6	25,0	60,0	10,5	115,0	15	~1,8 kg.	150	~18,0 kg.
BKP-D/150-M12/SD		M12	16,6	25,0	60,0	13,0	115,0	15	~1,8 kg.	150	~18,0 kg.
BKP-D/185-M08	185	M08	18,5	32,0	60,0	8,5	122,0	8	~1,8 kg.	80	~18,0 kg.
BKP-D/185-M10		M10	18,5	32,0	60,0	10,5	122,0	8	~1,8 kg.	80	~18,0 kg.
BKP-D/185-M12/SD		M12	18,5	32,0	60,0	13,0	122,0	8	~1,8 kg.	80	~18,0 kg.
BKP-D/240-M08	240	M08	21,0	32,0	60,0	8,5	122,0	8	~1,7 kg.	80	~17,0 kg.
BKP-D/240-M10		M10	21,0	32,0	60,0	10,5	122,0	8	~1,7 kg.	80	~17,0 kg.
BKP-D/240-M12/SD		M12	21,0	32,0	60,0	13,0	122,0	8	~1,7 kg.	80	~17,0 kg.
BKP-D/300-M08	300	M08	23,0	34,0	62,0	8,5	125,0	8	~1,8 kg.	80	~18,0 kg.
BKP-D/300-M10		M10	23,0	34,0	62,0	10,5	125,0	8	~1,8 kg.	80	~18,0 kg.
BKP-D/300-M12/SD		M12	23,0	34,0	62,0	13,0	125,0	8	~1,8 kg.	80	~18,0 kg.
BKP-D/400-M12/SD	400	M12	26,0	38,0	70,0	13,0	159,0	5	~1,9 kg.	50	~19,0 kg.
BKP-D/500-M18/SD	500	M18	29,0	47,0	75,0	19,0	167,0	3	~1,8 kg.	30	~18,0 kg.
BKP-D/625-M20/SD	625	M20	34,0	54,0	80,0	21,0	200,0	8	~6,8 kg.	16	~13,8 kg.

BKP-D SPECIFICATIONS

MATERIAL	ELECTROLYTIC COPPER / ALUMINIUM
COATING	NATURAL BRIGHT
JOINT	CLAMP COUPLING
COMPLY WITH DIN 48201 ALUMINIUM CABLE	
CONFORMED TO DIN 46329 TUBE DIMENSIONS	

